



**SILENT
KNIGHT**

by Honeywell

IntelliKnight® 5808 Single Loop Addressable Fire Alarm Control System

The convenience of an addressable fire alarm control panel in a cost-effective easy to use package.

IntelliKnight Model 5808 is a 127 point class leading single loop addressable fire alarm control/communicator system. 5808 provides you with the revolutionary value and performance of addressable sensing technology combined with exclusive, built-in digital communication, distributed intelligent power, easy to use interface. Powerful features such as drift compensation and maintenance alert are delivered in this powerful FACP from Silent Knight.

For more information about the IntelliKnight system, or to locate your nearest source, please call 1-800-328-0103.

Description

The basic 5808 system can be enhanced by adding modules such as 5860 remote annunciator, 5824 serial/parallel printer interface module (for printing system reports), and 5496 intelligent power module. 5808 supports Hochiki or SK protocol devices. 5808 also features a powerful built-in dual line fire communicator that allows for reporting of all system activity to a remote monitoring location.

Features

- Built-in support for up to 99 SK detectors *and* 99 SK modules.
- Built in support for 127 Hochiki SD devices.
- Up to 125 zones and 125 output groups.
- Uses standard wire—no shielded or twisted pair required
- Built-in digital communicator.
- Central station reporting by point or by zone
- Supports Class B (Style 4) and Class A (Style 6 or 7) configuration for SLC.
- Distributed, intelligent power.
- Drift compensation.
- 13 pre-programmed output cadences, (including ANSI-3.41), and 4 programmable outputs.
- Notification circuits can be configured as 2 Class A (Style Z) or 4 Class B (Style Y), or auxiliary power for resettable, constant, or door holder power.
- Built-in annunciator with 80-character LCD display.
- RS-485 bus provides communication to system accessories.
- Built-in RS-232 and USB interface for programming via a PC.
- Upload or download programming, event history, or detector status via remote or direct connection.
- Improvements in SKSS deliver five times faster upload/downloads.
- Built-in synchronization for appliances from AMSECO, Gentex®, Faraday, System Sensor®, and Wheelock®.
- One Form C trouble relay rated at 2.5A at 27.4 VDC and two Form C programmable relays rated at 2.5A at 27.4 VDC.



Model 5808

- Programmable date setting for Daylight Saving Time
 - Plex-2 door option combines a dead front cabinet door with a clear window, limiting access to the panel while providing single button operation of the reset and silence functions.
- Integrated dead front panel protects operator from exposure to electrical components.
- The FACP enclosure features a Plexiglass® viewing window to protect annunciator.
 - Acknowledge function allows operator to keep track of event status.

Installation


The 5800 can be surface or flush mounted.

Compatibility

The 5808 SLC supports multiple device types of the *same* protocol:

- SK (System Sensor)
- Hochiki SD

You cannot mix SD and SK devices on a FACP.



Specifications

Electrical

Primary AC: 120 VRMS at 50/60 Hz, 2.75A

Total Accessory Load: 6A @ 27.4 VDC

Notification Power: 6A @ 27.4 VDC, power-limited

Standby Current: 170 mA

Alarm Current: 325 mA

Notification & Auxiliary Circuits: 3A @ 27.4 VDC per circuit, power-limited

Battery Charging Capacity: 7.0-35 AH

Battery Size: 18 AH max. allowed in FACP. Larger capacity batteries can be housed in an RBB accessory cabinet

Physical

Flush Mount Dimensions: 14.5" W x 24.75" H x 3.5" D (36.8 W x 62.9 H x 8.73 D cm)

Overall Dimensions: 16" W x 26.4" H x 4.65" D (40.6 W x 67 H x 11.8 D cm)

Weight: 28 lbs. (12.8 kg)

Color: Red

Telephone Requirements:

FCC Part 15 and Part 68 approved
Type of Jack: RJ31X (two required)

Approvals

NFPA 13, NFPA 15, NFPA 16, NFPA 70, & NFPA 72: Central Station; Remote Signalling; Local Protective Signalling Systems; Auxiliary Protected Premises Unit; & Water Deluge Releasing Service. Suitable

for automatic, manual, waterflow, sprinkler supervisory (DACT non-coded) signalling services.

UL Listed
CSFM 7165-0559:0142;
MEA 429-92-E Vol. XIV

S-BUS Accessories

5860/R Remote Fire Annunciator

Features the same 80 character backlit LCD display keypad and firefighter's key switch as the 5808. 5860 is gray and 5860R is red.

5496 Intelligent Power Module

A 6 amp notification power expander that provides four additional power-limited notification appliance circuit outputs.

5880 LED/IO Module

Features 40 LED outputs, 8 normally open dry contact inputs and one piezo output.

5865-3 and 5865-4 Remote LED Annunciator

Features 30 programmable LED (15 red and 15 yellow) outputs and a piezo sounder. The 5865-4 adds a silence and reset switch to the package.

5824 Serial/Parallel Printer Interface Module

Provides one parallel and one RS-232 serial port for connecting a printer to 5808. Use to print a real-time log of system events, detector status reports, and event history.

5883 Relay Board

Features 10 general purpose Form C relays. Used with 5880 module.

Miscellaneous Accessories

5660 Silent Knight Software Suite

PC-base software for FACP programming. Upload and view panel account information, event history, and detector status.

5670 Silent Knight Software Suite

End-user facility management software allows viewing of detector status and event history via modem or direct connection.

Plex-2 Door

Dead front cabinet door with clear window to limit access to the FACP.

RBB

Remote Battery Box Accessory Cabinet. Use if backup batteries are too large to fit into FACP cabinet. Dimensions:

16" W x 10" H x 6" D (406 mm W x 254 mm H x 152 mm D)

Hochiki and SK Devices

See the specification sheets listed below for a complete listing of the Hochiki and SK devices.

53624 Hochiki SD Devices data sheet

53623 SK Device Protocol Devices data sheet

IntelliKnight & JumpStart are Registered Trademarks of Silent Knight Flexput is a Trademark of Silent Knight



This document is not intended to be used for installation purposes. We try to keep our product information up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice. For more information, contact Silent Knight 12 Clintonville Road, Northford, CT 06472-1610. Phone: (800) 328-0103, Fax: (203) 484-7118. www.silentknight.com

MADE IN AMERICA

350386 Rev. H
© 2011 Honeywell International Inc.